

FIELD OF THE INVENTION

5

10

15

In order to uniquely determine the axial location of the cutting insert an axial stop is provided in the insert pocket. In some prior art cutting tool assemblies the stop is located on one of the clamping surfaces of the upper and lower clamping jaws. In such cases, the cutting insert has to be designed with an appropriate protrusion or recess, on the corresponding insert clamping abutment surface, for engaging the stop. In other prior art cutting tool assemblies, the stop is located at the rear of the insert pocket and the axial location of the cutting insert is fixed when

1 a section of the rear surface of the cutting insert abuts the stop. This arrangement
has two disadvantages. First, it restricts the shape of the rear surface of the cutting
insert. For double-ended grooving cutting inserts the rear surface is the non-
operative front relief surface. Hence, this arrangement restricts the shape of the
5 front relief surface of the cutting insert. Second, if the end portion of the cutting
insert, associated with the operative cutting edge, were to break during a cutting
operation, the section of the relief surface which would abut the stop on indexing
the cutting insert, may well become damaged, in which case the cutting insert could
not be indexed, preventing use of the cutting edge associated with the non-damaged
10 end portion of the cutting insert.

To stabilize the cutting insert in the direction perpendicular to the axial
direction, the clamping abutment surfaces of the cutting insert are formed with V-
shaped protrusions (or grooves) and the clamping surfaces of the insert holder's
jaws are formed with matching V-shaped grooves (or protrusions). According to
15 some embodiments of such cutting tool assemblies, the cutting inserts have a stop-
engaging protrusion (or recess) on one of their clamping abutment surfaces and the
insert holders having a corresponding stop-engaging recess (or protrusion) on one
of the clamping surfaces of one of their clamping jaws. The presence of such stop-
engaging protrusions (or recesses) can be disadvantageous.

20 It is an object of the present invention to provide a double-ended
grooving cutting insert that substantially overcomes the above mentioned
disadvantages.

It is also an object of the present invention to provide an insert holder
for retaining the above-mentioned grooving cutting insert.

25

SUMMARY OF THE INVENTION

In accordance with the present invention there is provided a cutting
insert comprising a central body portion extending between two opposite end
portions, each end portion being provided with a cutting edge; the central body

portion being provided with upper and lower clamping abutment surfaces with first and second side surfaces extending therebetween; at least one of the first and second side surfaces being provided with an axial location member.

5 In accordance with one embodiment, the axial location member is a protrusion.

Generally, the protrusion is square shaped.

In accordance with another embodiment of the present invention, the axial location member is a recess.

10 Preferably, the upper and lower clamping abutment surfaces are sloped, defining therebetween a variable distance, so that when the cutting insert is viewed in an end view the distance between the upper and lower clamping abutment surfaces is a maximum at the first side surface and a minimum at the second side surface.

15 If desired, the upper and lower clamping abutment surfaces have the form of V-shaped protrusions.

Further if desired, the upper and lower clamping abutment surfaces have the form of V-shaped grooves.

There is also provided in accordance with the present invention a cutting tool assembly comprising:

20 a cutting insert holder; and
a cutting insert;

the cutting insert holder comprising:

an upper clamping jaw having an upper clamping surface;
a lower base jaw having a lower clamping surface;
25 at least one clamping screw passing through the upper clamping jaw and threadingly connected to the lower base jaw;
an insert holder inner side surface extending between the upper and lower clamping surfaces;
an insert pocket bound on two opposite sides by the upper and lower

clamping surfaces and bound on a third side extending between the two opposite sides by the insert holder inner side surface; the insert holder inner side surface being provided with a positioning member;

the cutting insert comprising:

- 5 a central body portion extending between two opposite end portions, each end portion being provided with a cutting edge; the central body portion being provided with upper and lower clamping abutment surfaces with first and second side surfaces extending therebetween; at least one of the first and second side surfaces being provided with an axial location member;

- 10 wherein the upper clamping abutment surface abuts the upper clamping surface, the lower clamping abutment surface abuts the lower clamping surface and the positioning member engages the axial location member whereby the axial location of the cutting insert is fixed.

- 15 In accordance with one embodiment, the axial location member is a protrusion and the positioning member is a rear surface of a recess in the insert holder inner side surface.

Generally, the protrusion is square shaped and the recess has a generally matching square shaped cross section.

- 20 In accordance with another embodiment, the axial location member is a recess and the positioning member is a protrusion on the insert holder inner side surface.

- 25 Preferably, the upper and lower clamping abutment surfaces are sloped, defining therebetween a variable distance, so that when the cutting insert is viewed in an end view the distance between the upper and lower clamping abutment surfaces is a maximum at the first side surface and a minimum at the second side surface and the upper and lower clamping surfaces of the upper clamping jaw and the lower base jaw, respectively, are matchingly sloped.

If desired, the upper and lower clamping abutment surfaces have the form of V-shaped protrusions and the upper and lower clamping surfaces of the

upper clamping jaw and the lower base jaw, respectively, have the form of matching V-shaped grooves.

Further if desired, the upper and lower clamping abutment surfaces have the form of V-shaped grooves and the upper and lower clamping surfaces of the upper clamping jaw and the lower base jaw, respectively, have the form of matching V-shaped protrusions.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a right perspective view of a cutting tool assembly in accordance with one preferred embodiment of the present invention with the cutting insert removed from the insert holder;

Fig. 2 is a left perspective view of the cutting tool assembly shown in Fig. 1;

Fig. 3a is a side view of the cutting insert shown in Figs. 1 and 2;

Fig. 3b is a top view of the cutting insert shown in Figs. 1 and 2;

Fig. 3c is a front view of the cutting insert shown in Figs. 1 and 2;

Fig. 4a is a partial side view of the insert holder shown in Figs. 1 and 2;

Fig. 4b is a cross-sectional view along line IVb-IVb in Fig. 4a;

Fig. 4c is a partial front view of the insert holder shown in Figs. 1 and 2;

Fig. 5 is a right perspective view of a cutting tool assembly in accordance with another preferred embodiment of the present invention with the cutting insert removed from the insert holder;

Fig. 6a is left perspective view of the cutting insert shown in Fig. 5;

Fig. 6b is a side view of the cutting insert shown in Figs. 5 and 6a;

Fig. 7 is a side view of a cutting tool assembly in accordance with the present invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are sloped and the clamping surfaces of the insert holder's jaws are formed with matching slopes;

Fig. 8 is a side view of a cutting tool assembly in accordance with the present invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are formed with V-shaped protrusions and the clamping surfaces of the insert holder's jaws are formed with matching V-shaped grooves;

Fig. 9 is a side view of a cutting tool assembly in accordance with the present invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are formed with V-shaped grooves and the clamping surfaces of the insert holder's jaws are formed with matching V-shaped or protrusions;

Fig. 10a is a front view of a cutting insert having a protrusion on each of the side surfaces of the central body portion;

Fig. 10b is a side view of the cutting insert shown in Fig. 10a;

Fig. 11a is a front view of a cutting insert having a recess in each of the side surfaces of the central body portion; and

Fig. 11b is a side view of the cutting insert shown in Fig. 11a.

DETAILED DESCRIPTION OF THE INVENTION

Attention is first drawn to Figs. 1 to 4c, showing a cutting tool assembly in accordance with the present invention comprising a cutting insert holder 22 and a cutting insert 24. The cutting insert holder 22 comprises an upper clamping jaw 26 having an upper clamping surface 28 and a lower base jaw 30 having a lower clamping surface 32. Two clamping screws 34 are used to securely clamp the cutting insert 24 between the upper and lower clamping surfaces. Each clamping screw 34 passes through a through bore 36 in the upper clamping jaw 26 and is threadingly connected to the lower clamping jaw via a threaded bore 38 in the lower base jaw 30. Between the upper and lower clamping surfaces extends an insert holder inner side surface 40. An insert pocket 42, for receiving and retaining the cutting insert 24, is bound on two opposite sides by the upper and lower

clamping surfaces and on a third side, extending between the two opposite sides, by the insert holder inner side surface **40**. The insert holder inner side surface is provided with a recess **44** having a rear surface **45** forming a positioning member for the determination of the axial location of the cutting insert.

5 The cutting insert **24** comprises a central body portion **46** extending between two opposite end portions **48**, **50**, the end portions being provided with cutting edges **52**. The central body portion **46** has upper and lower clamping abutment surfaces **54**, **56** with first and second side surfaces **58**, **60**, extending therebetween. The first side surface **58** is provided with a protrusion **62** forming
10 an axial location member for the cutting insert. The protrusion **62**, in the embodiment shown, is square shaped and the recess **44** has a matching square shaped cross section for receiving the protrusion **62**.

 When the cutting tool assembly is assembled, the upper clamping abutment surface **54** of the cutting insert **24** abuts the upper clamping surface **28**
15 of the upper clamping jaw **26**, the lower clamping abutment surface **56** of the cutting insert abuts the lower clamping surface **32** of the base jaw **30** and the protrusion **62** engages the rear surface **45** of the recess **44**, whereby the axial location of the cutting insert **24** is fixed.

 It should be noted that the cutting insert **24** has 180° rotational
20 symmetry about an axis perpendicular to a longitudinal plane **P** of the cutting insert and passing through the center of the protrusion **62**. Hence, for a given orientation of the cutting insert, as best seen in Fig. 3a, one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the
25 lower clamping abutment surface **56**. Clearly, as best seen in Figs. 1 and 2, the upper cutting edge is the operative cutting edge. It should further be noted that since the present invention is directed to the axial location of the cutting insert and not to its specific shape or function, the cutting edges and the associated rake and relief surfaces are only shown schematically and it will be apparent that any

required form of rake and relief surface and associated cutting edge can be used.

Attention is now drawn to Figs. 5 to 6b showing a cutting insert holder **64** and an associated cutting insert **66** in accordance with another embodiment of the present invention. In this embodiment the axial location of the cutting insert **66** is determined by the engagement of a protrusion **68** on the insert holder inner side surface **40** by a recess **70** in the first side surface **58** of the central body portion **46** of the cutting insert. As shown in Figs. 5 to 6b, there are two recesses **70** on the first side surface **58** of the central body portion **46**. Therefore, as with the above described first embodiment, the cutting insert has 180° rotational symmetry about an axis passing through the geometrical center of the side surfaces **58**, **60** of the central body portion **46** and perpendicular to a longitudinal plane of the cutting insert **66**. Hence, for a given orientation of the cutting insert, as best seen in Fig. 6b (which is similar to Fig. 3a), one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the lower clamping abutment surface **56**.

In the embodiments shown in Figs. 1 to 6b, the geometry of the upper and lower clamping abutment surfaces **54**, **56** is not detailed and these surfaces are shown schematically to be flat and parallel. Figs. 7 to 9 show different possible geometries for the upper and lower clamping abutment surfaces. Although these geometries are exemplified for the embodiment of the invention shown in Figs. 1 to 4c, they apply equally well to the embodiment of the invention shown in Figs. 5 to 6b. Preferably, as shown in Fig. 7, the upper and lower clamping abutment surfaces **54**, **56** are sloped so that when the cutting insert is viewed in an end view the distance between them is a maximum at the first side surface **58** and a minimum at the second side surface **60**. The upper and lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have matching slopes. Hence, when the cutting insert **24** is clamped in the insert pocket **42** of the cutting insert holder **22**, the upper

clamping abutment surface **54** of the cutting insert abuts the upper clamping surface **28** of the upper clamping jaw **26**, the lower clamping abutment surface **56** of the cutting insert abuts the lower clamping surface **32** of the lower base jaw **30**, the protrusion **62** on the first side **58** of the central body portion **46** of the cutting insert abuts the rear surface **45** of the recess **44** and the first side surface **58** abuts the insert holder side surface **40**.

If desired, as shown in Fig. 8, the upper and lower clamping abutment surfaces **54**, **56** have the form of V-shaped protrusions and the upper and lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have the form of matching V-shaped grooves.

Further if desired, as shown in Fig. 9, the upper and lower clamping abutment surfaces **54**, **56** have the form of V-shaped grooves and the upper and lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have the form of matching V-shaped protrusions.

The cutting inserts **24**, **66** described above have axial location members only on one side surface **58** of the central body portion **46**. As a result, for a given orientation of the cutting insert, one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the lower clamping abutment surface **56**. Attention is now drawn to Figs. 10a to 11b. Figs. 10a and 10b show a cutting insert **72** having two protrusions **62** both constituting axial location members. One protrusion **62** is on the first side surface **58** and the other protrusion **62** is on the second side surface **60**. As seen in Fig. 10b, both cutting edges **52** are upper cutting edges, associated with the upper clamping abutment surface **54**. Similarly, Figs. 11a and 11b show a cutting insert **74** having two axial location members **70'**, **70''**, both recesses. One recess **70'** is on the first side surface **58** and the other recess **70''** is on the second side surface **60**. The dashed lines represent a hidden recess. As seen in Fig. 11b, both cutting edges **52** are upper cutting edges associated with the upper clamping abutment

surface **54**.

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications can be made without departing from the spirit or scope of the invention as hereinafter
5 claimed. For example, the shape of the axial location member of the cutting insert and the positioning member of the cutting insert holder do not necessarily have to be square shaped, they can be round, elliptical or any other convenient shape.

50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000